

624

Firesleeve



Firesleeve will protect hose from direct flame. Firesleeve is constructed of a uniform single layer of braided fiberglass tubing impregnated with flame resistant silicone rubber. Temperature range of -53.8°C to +260°C (-65°F to +500°F).


624		
Part #	Nominal Sleeve I.D.* "B"	
	mm	in
624-5	7.9	0.31
624-7	11.2	0.44
624-8	12.7	0.50
624-9	14.2	0.56
624-10	15.7	0.62
624-11	17.5	0.69
624-12	19.0	0.75
624-13	20.6	0.81
624-14	22.3	0.88
624-16	25.4	1.00
624-18	28.4	1.12
624-20	31.7	1.25
624-22	35.0	1.38
624-24	38.1	1.50
624-26	41.1	1.62
624-28	44.4	1.75
624-30	47.7	1.88
624-32	50.8	2.00
624-38	60.4	2.38
624-42	66.5	2.62
624-46	73.1	2.88
624-50	79.2	3.12
624-54	85.8	3.38
624-60	95.2	3.75

FC425

Nylon abrasion sleeve meets MSHA requirements



Nylon sleeve protects hose from abrasion and allows bundling of hose lines.



FC425		
Part #	Nominal Sleeve I.D.* "B"	
	mm	in
FC425-12	18.0	0.71
FC425-16	25.4	1.00
FC425-18	28.7	1.13
FC425-20	31.7	1.25
FC425-24	40.4	1.59
FC425-28	44.4	1.75
FC425-32	52.6	2.07
FC425-38	60.4	2.38
FC425-40	64.5	2.54
FC425-46	72.6	2.86
FC425-54	84.8	3.34
FC425-59	93.0	3.66

*The maximum O.D. of hose fittings must be allowed for if fittings are to be covered.

900729

Support clamp

These lightweight vinyl-coated steel support clamps are designed to support hose where long runs are necessary.

This clamp not only furnishes a cleaner installation, but prevents damage, exposure and chafing. The lining will withstand high ambient temperatures. Bolt hole dia: Clamp dash no. -01 thru -8, -18 thru -23 is M10; -9 thru -17, -24 thru -31 is M12.

