


GC3425-size (6000 psi) Half Flange SAE J518 C Code 62



Part Number	Flange	Size	Max. Oper. Press. bar	A mm	B mm	E Ø mm	H mm	Bolt Ø metric/inch	Part Number O-Ring ¹ *	D Ø mm	S Ø mm
GC3425-8	1/2"	-8	415	40,5	9,1	8,4	16,0	M8 / 5/16"	05.018-210	18,6	3,5
GC3425-12	3/4"	-12	415	50,8	11,9	10,5	19,0	M10 / 3/8"	05.018-214	25,0	3,5
GC3425-16	1"	-16	415	57,2	13,9	12,0	24,0	7/16"	05.018-219	32,9	3,5
GC3425-16.1	1"	-16	415	57,2	13,9	13,0	24,0	M12	05.018-219	32,9	3,5
GC3425-20	1 1/4"	-20	415	66,7	15,9	13,5	27,0	1/2"	05.018-222	37,7	3,5
GC3425-20.1	1 1/4"	-20	415	66,7	15,9	15,0	27,0	M14	05.018-222	37,7	3,5
GC3425-24	1 1/2"	-24	415	79,4	18,2	17,0	30,0	M16 / 5/8"	05.018-225	47,2	3,5
GC3425-32	2"	-32	415	96,8	22,2	20,0	36,5	3/4"	05.018-228	56,7	3,5
GC3425-32.1	2"	-32	415	96,8	22,2	21,0	36,5	M20	05.018-228	56,7	3,5



* For Phosphate Esther Fluids, basic O-Ring No. 22566, i.e.: 22566-214.

* Für Einsätze mit Druckflüssigkeiten auf Phosphatester-Basis lautet die O-Ring Grundnummer 22566, z.B. 22566-214.

* La référence de base pour les esters de phosphate est 22566. Exemple: 22566-214.

* Per impiego con liquidi a pressione a base di esteri fosforici: numero base dell'O-ring 22566, ad esempio 22566-214.

* Para el empleo con fluidos a presión a base esterfosfóricos el número básico del anillo en O es 22566, por ej. 22566-214.